

Xprinter®

Cloud Printing



PC, Ipad, Mobile



GPRS



WIFI



XP-V330L

Thermal Receipt Printer

- Horizontal, Wall-hanging design
- Easy of use feature include drop in paper load and auto cutter.

APPLICATIONS



Shopping



Mart



Hospital



Coffee Shop



Restaurant



Ticketing




Express



Factory

XP-V330L



Model	XP-V330L
Printing method	Direct thermal
Paper width	79.5±0.5mm
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm
Column capacity	576 dots/line(adjustable by command)
Printing speed	260 mm/s Max.
Interface	USB+LAN+WiFi / USB+LAN+4G
Line spacing	3.75mm(Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)
Cutter	
Auto cutter	Partial
Barcode Character	
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR CODE / PDF417
Input buffer	128 Kbytes
NV Flash	256 Kbytes
Power	
Power adaptor	Input: AC 100-240V/50~60Hz; Output: DC 24V/2.5A
Printer input	DC 24V/2.5A
Cash drawer	DC 24V/1A
Physical characteristics	
Weight	1.0 Kg
Dimensions	183.3 ×140×141.5 mm (D×W×H)
Environmental Requirements	
Operation environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 90%)
Reliability	
Cutter life	1.5 million cuts
Printer head life	150Km
Networks	
GSM/GPRS	850 / 900 / 1800 / 1900MHz
Software	
Emulation	ESC/POS
Driver	Windows/JPOS/ OPOS/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS/Android/Windows



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net

